



Portable SVP

- Self recording and/or direct reading
- High-precision measurement using direct sounding
- Handy and portable, easy-to-use
- Integrated battery, giving long operation
- Integrated verification procedures
- PC software included
- Based on proven, reliable design
- Includes external battery charger and power supply

RESON's Portable SVPs include a range of models that use direct sounding technology to measure sound velocity while a vessel is underway.

SVP 14/15 models measure sound velocity for shallow depths (temperature measurement for these models is available as an option). Housed in a compact yet easy-to-use unit, all Portable SVPs can operate in two modes:

- 1) They can send sound velocity data directly via cable to an external device
- 2) They all can operate autonomously by using the internally sealed and rechargeable batteries and storing data collected in internal memory

All RESON SVPs also include PC-based software for logging and presentation.





Portable SVP

Sound Velocity Profilers For Depth

Control:
PC software package for logging and presentation

Scope of delivery:
For SVP 14/15 & SVP 14T/15T: SVP unit, SVPD-10 unit, 3m power cable, 2m subconn cable, 3m D-SUB 9-pin interface cable (PC), and PC software for logging and presentation.

SPECIFICATION SVP	14/15
Sound velocity	
Range:	1350-1600m/sec
Resolution:	0.1m/sec
Accuracy:	± 0.25m/sec
Depth Range:	
SVP 14 :	40m in 0.5m steps
SVP 15 :	200m in 0.5m steps
Measurement:	Pressure sensor
Accuracy:	± 0.10m + 0.2% of measured depth
Temperature accuracy:	± 0.4°C (SVP 14T/15T models only)
Barometric adjustment:	Self-adjusting zero point
Ultrasonic transmitter:	
Power:	1W
Output rate:	10Hz
Frequency:	2MHz (nominal)
Data transmission:	RS-232 at 9600 Baud 7 data bits, odd parity, 2 stop bits
Memory capacity:	80 measurements (SVP 14) 400 measurements (SVP 15)
Operating temperature:	0 to +45°C
Power Consumption:	100mA
Supply:	115/230VAC with 2m cable
Housing:	Black polycarbonate
Connector:	6 pin Subcon
Weight:	5.0kg
Tube diameter:	90mm (3.5 inches)
Max. diameter:	100mm (4 inches)
Length:	550mm (22 inches) includes reflector



RESON reserves the right to change specifications without notice. © 2006 RESON A/S
For Acoustical Measurement Accuracy please refer to www.reson.com or contact sales.

RESON A/S
Denmark
Tel: +45 4738 0022
E-mail: reson@reson.com

RESON Inc.
USA
Tel: +1 805 964-6260
E-mail: sales@reson.com

RESON Offshore Ltd.
United Kingdom
Tel: +44 1224 709 900
E-mail: sales@reson.co.uk

RESON GmbH
Germany
Tel: +49 431 720 7180
E-mail: reson@reson-gmbh.de

RESON B.V.
The Netherlands
Tel: +31 (0) 10 245 1500
E-mail: info@reson.nl

RESON (Pte.) Ltd.
Singapore
Tel: +65 6725 9851
E-mail: sales@reson.com

www.reson.com